


HELUTHERM® 145

Single core, flexible, cross-linked, halogen-free



Technical data

- Halogen-free single core with increased heat resistance
- **Temperature range**
flexing -35°C to +120°C
fixed installation -55°C to +145°C
- **Nominal voltage**
up to 1 mm² U₀/U 300/500 V
from 1,5 mm² U₀/U 450/750 V
at fixed and protected installation
from 1,5 mm² U₀/U 600/1000 V
- **Test voltage**
3500 V
- **Minimum bending radius**
flexing 8x core Ø
fixed installation 4x core Ø
- **Caloric load values**
see "Technical Information"
- **Current rating**
see "Technical Information"
- **Approval**
DNV GL

Cable structure

- Tinned copper conductor, fine wire acc. to DIN VDE 0295 cl.5 / IEC 60228 cl.5
 - Core insulation: cross-linked polyolefin-copolymer
 - Core identification: see table below
- ### Tests
- Flame test acc. to
DIN VDE 0482-332-3-22 /
DIN EN 60332-3-22 / IEC 60332-3-22
 - Flame test acc. to
DIN VDE 0482-332-1-2 /
DIN EN 60332-1-2 / IEC 60332-1-2
 - Halogen-free acc. to
DIN VDE 0482-754-1 /
DIN EN 60754-1 / IEC 60754-1
 - Corrosiveness of combustion gases acc. to DIN VDE 0482-754-2 /
DIN EN 60754-2 / IEC 60754-2
 - Smoke density acc. to
DIN VDE 0482-1034-1+2 /
DIN EN 61034-1+2 / IEC 61034-1+2
 - Fire protection on railway vehicles acc. to EN 45545-2

Properties

- No flame propagation
- Good abrasion and notch resistance
- Good resistance to weathering
- Resistant to UV radiation and ozone
- Resistant to melting, even when in contact with a soldering iron with temperatures from 300°C to 380°C
- Due to the high temperature profile the cross section of conductor can under certain circumstances be reduced, hereby enabling a saving in space requirement and weight
- The materials used during manufacturing are cadmium-free, contain no silicone and are free from substances harmful to the wetting properties of lacquers

Application

These temperature resistant single core are used for the internal wiring of lighting fixtures, heaters, electrical machinery, switching systems and distributors in equipment and plant and machinery, suitable for laying in tubes on and under plaster, in closed installation ducts, as well as for traffic systems and outdoor applications. Not suitable for direct laying in cable ladders and cable trays, except as a potential equalisation cable. These single core are characterised by their amazingly high long-time resistance to temperature and feature among the leading halogen-free, flame resistant products in the world.

CE = Product conforms with Low-Voltage Directive 2014/35/EU.

Cross-sec. mm ²	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km	BK	GN-YE	BU	BN	RD	WH	GY	VT	YE	GN	D-BU	OG	BEIGE	2-col.
Part no. 0,25	1,6	2,4	4,0	50999	50998	51070	51071	51072	51073	51074	51075	51076	51078	51079	51077	51164	51165
Part no. 0,34	1,7	3,2	5,0	51167	51166	51168	51169	51170	51171	51172	51173	51174	51176	51177	51175	51178	51179
Part no. 0,5	1,9	4,8	7,0	51281	51280	51282	51283	51284	51285	51286	51287	51288	51290	51291	51289	51292	51293
Part no. 0,75	2,2	7,2	11,0	51295	51294	51296	51297	51298	51299	51300	51301	51302	51304	51305	51303	51306	51307
Part no. 1	2,5	9,6	14,0	51309	51308	51310	51311	51312	51313	51314	51315	51316	51318	51319	51317	51320	51321
Part no. 1,5	2,9	14,4	20,0	51323	51322	51324	51325	51326	51327	51328	51329	51330	51332	51333	51331	51334	51335
Part no. 2,5	3,5	24,0	30,0	51337	51336	51338	51339	51340	51341	51342	51343	51344	51346	51347	51345	51348	51349
Part no. 4	4,3	38,0	47,0	51351	51350	51352	51353	51354	51355	51356	51357	51358	51360	51361	51359	51362	51363
Part no. 6	5,0	58,0	72,0	51365	51364	51366	51367	51368	51369	51370	51371	51372	51374	51375	51373	51376	51377
Part no. 10	6,3	96,0	120,0	51379	51378	51380	51381	51382	51383	51384	51385	51386	51388	51389	51387	51390	51391

Continuation ►

HELUTHERM® 145

Single core, flexible, cross-linked, halogen-free



Cross-sec. mm ²	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km	BK	GN-YE	BU	BN	RD	WH	GY	VT	YE	GN	D-BU	OG	BEIGE	2-col.
Part no. 16	7,3	154,0	182,0	51420	51419	51421	51422	51423	51424	51425	51426	51427	51429	51430	51428	51431	51432
Part no. 25	9,6	240,0	272,0	51434	51433	51435	51436	51437	51438	51439	51440	51441	51443	51444	51442	51445	51446
Part no. 35	10,8	336,0	371,0	51448	51447	51449	51450	51451	51452	51453	51454	51455	51457	51458	51456	51459	51460
Part no. 50	12,6	480,0	530,0	51462	51461	51463	51464	51465	51466	51467	51468	51469	51471	51472	51470	51473	51474
Part no. 70	14,6	672,0	730,0	51476	51475	51477	51478	51479	51480	51481	51482	51483	51485	51486	51484	51487	51488
Part no. 95	16,5	912,0	964,0	51490	51489	51491	51492	51493	51494	51495	51496	51497	51499	51500	51498	51501	51502
Part no. 120	18,0	1152,0	1235,0	51504	51503	51505	51506	51507	51508	51509	51510	51511	51513	51514	51512	51515	51516
Part no. 150	20,0	1440,0	1523,0	51518	51517	51519	51520	51521	51522	51523	51524	51525	51527	51528	51526	51529	51530
Part no. 185	22,2	1776,0	1850,0	51532	51531	51533	51534	51535	51536	51537	51538	51539	51541	51542	51540	51543	51544
Part no. 240	24,5	2304,0	2432,0	51546	51545	51547	51548	51549	51550	51551	51552	51553	51555	51556	51554	51557	51558

Dimensions and specifications may be changed without prior notice. (RK01)