

OP

	XX Number of contacts	X Pitch	X Pin length	X Pin plating	X Material of body	X	X	X	X	X
Solid Block	2 3.5/.138"	2 L=12.5mm(UpΦ1.3 DownΦ1.0)(DIMA=3.5) B L=10.0mm(Φ1.0)(DIMA=3.5) (only pitch 3.5 used for EH)	0 Tin 1 Gold plating 10u" 2 Gold flash	0 PA66 1 PA46	0000 Standard Any special item by customer request, please contact sales department.	G	ROHS compliant (lead<4%) In copper alloy			
02 2 contacts	3 7.0/.276"	3 L=11.5mm(Φ1.3)(DIMA=1.9)								
03 3 contacts	4 3.81/.15"									
.. ..	5 7.62/.30"									
24 24 contacts (pitch 3.5&3.81)	6 8.0/.315"	3 L=11.5mm(Φ1.3)(DIMA=1.9)								
20 20 contacts (pitch 8.0)										
12 12 contacts (pitch 7.0&7.62)										

OP

	XX Number of contacts	X Pitch	X Pin length	X Pin plating	X Material of body	X	X	X	X	X
Solid Block	0 5.0/.197"	0 L=12.5mm(Φ1.3)(DIMA=3.5) 1 L=13.0mm(UpΦ1.3 DownΦ1.0)(DIMA=4.3) 2 L=12.5mm(UpΦ1.3 DownΦ1.0)(DIMA=3.5) 3 L=11.5mm(Φ1.3)(DIMA=1.9) 4 L=14.2mm(Φ1.3)(DIMA=2.9) 5 L=17.5mm(Φ1.3)(DIMA=3.5) 6 L=20.0mm(Φ1.3)(DIMA=3.5) 7 L=18.0mm(UpΦ1.3 DownΦ1.0)(DIMA=3.5) 8 L=16.2mm(UpΦ1.3 DownΦ1.0)(DIMA=3.5) 9 L=16.5mm(Φ1.3)(DIMA=3.5) A L=21.0mm(Φ1.1)(DIMA=4.4) C L=12.7mm(Φ1.1)(DIMA=4.4) D L=16.3mm(Φ1.1)(DIMA=4.4) F L=12.5*8.8mm Bend pin(Φ1.3) J L=13.0mm pin(Φ1.3)(DIMA=3.5) H L=25.5mm pin(Φ1.3)(DIMA=3.5) G L=17.9mm pin(Φ1.10)(DIMA=4.4) K L=12.0mm pin(UpΦ1.3 DownΦ1.0)(Round pin) M L=11.8mm pin(Φ1.1)(DIMA=4.0) U L=25.1mm pin(Φ1.0)(DIMA=4.0)	0 Tin 1 Gold plating 10u" 2 Gold flash	0 PA66 1 PA46	0000 Standard Any special item by customer request, please contact sales department.	G	ROHS compliant (lead<4%) In copper alloy			
02 2 contacts	1 10.0/.394"									
03 3 contacts	8 5.75/.226"									
.. ..										
24 24 contacts (pitch 5.0&5.75)										
12 12 contacts (pitch 10.0)										

OQ

	XX Number of contacts	X Pitch	X Body type	X Color	X PCB mounting	X	X	X	X	X
Solid Block	B 2.5/.098"	0 Open (pitch 5.0/7.5/7.62) 1 Close (pitch 2.5/5.0/7.5/7.62) 2 Close (pitch 3.5/3.81) 3 Open (pitch 5.08) 4 Close (pitch 5.08) 5 With flange (pitch 3.5/3.81/5.0/5.08/7.5/7.62)	0 Black 5 Green (RAL 6018/T) 6 Blue 8 Grey (RAL 7035/D) C Green (RAL 6018/U)	0 Vertical 1 Right angle	0000 Standard Any special item by customer request, please contact sales department.	G	ROHS compliant (lead<4%) In copper alloy			
02 2 contacts	3 3.81/.15"									
03 3 contacts	7 5.0/.197"									
.. ..	5 5.08/.20"									
24 24 contacts	A 7.5/.295"									
16 16 contacts (pitch 7.5&7.62)	0 7.62/.30"									

OQ
(With latch holder)

	XX Number of contacts	X Pitch	X Body type	X Color	X PCB mounting	X	X	X	X	X
Solid Block	1 3.5/.138"	7 With latch holder	0 Black 2 Red 3 Orange 4 Yellow 5 Green (RAL 6018/T) 6 Blue 8 Grey 9 White C Green (RAL 6018/U)	0 Vertical 1 Right angle	0000 Standard Any special item by customer request, please contact sales department	G	RoHS compliant (lead<4%) In copper Alloy			
02 2 contacts	3 3.81/.15"									
03 3 contacts	7 5.0/.197"									
.. ..	5 5.08/.20"									
24 24 contacts										